## 13" x 18" Capacity PLC Controlled, Full Cycle Semi-Automatic Operation



formerly model 1118 SA





Manufactured in the United States of America





### **Standard Features**

|  | PLC Controlled, Full Cycle Semi-Automatic Operation                  |    |  |
|--|--|----|--|
|  | Variable Hydraulic Feed Rate Control                                 |    |  |
|  | pring-Loaded Carbide Guides with Rollers                             |    |  |
|  | Combination Reduction Gearbox and Perimeter Ring Gear<br>Blade Drive | BI |  |
|  | Baldor® Motor<br>3hp Motor 3 Phase TEFC<br>2hp Single Phase ODP      | BI |  |
|  | Infinitely Variable Blade Speeds                                     | EI |  |
|  | Rite-Tension <sup>®</sup> Blade Tensioning Device                    |    |  |
|  | Wet Cutting System   | Co |  |
|  | Powered Blade Brush  |    |  |
|  | 110 Volts at Controls  | Vi |  |
|  | Overload and Undervoltage Protection                                 | Sv |  |
|  | Precision Ground Bed and Vise Jaws                                   | Fe |  |
|  | Quick Acting Vise/Air Powered  | Ba |  |
|  | Adjustable Stock Stop  | Be |  |
|  | Auto Shut-Off at End of Cut  | FI |  |
|  | OSHA Blade Guarding  | Sł |  |
|  | Tiger-Tooth <sup>®</sup> Bi-Metal Blade                              | 21 |  |
|  | Coolant for Initial Start-Up   |    |  |

# Available Factory Installed Options

- Flush Hose with 8.5 GPM Pump
- **Laser Line Pointer**
- Casters (Set of 4, 2 Locking)
- **NFPA Electrics (with Disconnect)**
- Work Light with Transformer
- Stock Stand, 18"
- 5' Non-Powered Roller Conveyor
- 10' Non-Powered Conveyors

**Please Contact Factory for Additional Options** 

#### **Specifications**

| Capacity           | Round 13"<br>Rectangular 13" x 18"<br>45° Angle 11" x 9-1/2" |
|--------------------|--|
| Blade Size         | 1" x .035" x 12'6" (150")                                    |
| Blade Speeds       | Infinitely Variable<br>70-375 SFPM                           |
| Blade Guides       | Carbide Guides with Rollers                                  |
| Blade Tension      | Manual Rite-Tension®   |
| Electrical Options | 115-208-230/60/1<br>208-230-460/60/3                         |
| Coolant System     | Tank Capacity 8 Gallons<br>Submersible Pump/3 GPM            |
| Vise Control       | Quick Acting/Manual Screw                                    |
| Swivel Vise        | To 45°   |
| Feed Control       | Variable Hydraulic/<br>Counterbalance Spring                 |
| Band Wheels        | 15" Diameter Cast Iron                                       |
| Bed Height         | 35"  |
| Floor Area         | 40"W x 84"L  |
| Shipping Weight    | 955 Lbs.   |
|                    |  |

## Other Models in the 1318 Family

Model 1338 with 38" Width Capacity

Model 1316S Swivel Head Miter Saw to 60°

All Models Available with PLC Controlled Semi-Automatic Operation

**The Model 1318-SA** provides the strength and precision of our popular manual saw with the convenience of true semi-automatic operation. The factory programmed PLC manages the saw head and bed vise improving both safety and productivity.

